



บริษัท ท็อปส์ ซินเนอร์จิสต์ จำกัด  
TOPS SYNERGIST CO., LTD.

## TECHNICAL DATA SHEET

# TOPS PC-174

**BONDING AGENT ( น้ำยาประสานคอนกรีต )**

### DESCRIPTION

TOPS PC-174 is a styrene-butadiene copolymer LATEX manufactured in Asia.

### APPLICATIONS

Suggested as a polymer for hydraulic cement mortars and concretes  
Recommended for use in repair/general purpose mortars and overlay applications

### FEATURES

- Excellent cement stability
- Increase adhesion to most substrates
- Increased water resistance
- Good mechanical stability
- Reduced water to cement ratio
- Increased resistance to freezing and thawing

### TYPICAL PROPERTIES

Polymer Type	Styrene butadiene
Nonvolatile Content, %	45.0 - 47.0
pH	8.5 – 10.5
Viscosity, Brookfield (cps)	100 – 500 cps
Tg, °C	+8

TOPS PC-174 contains an effective antifoam system. Avoid over-mixing.

### STORAGE AND HANDLING

Protect from freezing. Ideal storage temperature is 25°C . Stability at 25°C is 365 days when properly stored. **Read the TOPS PC-174 Material Safety DataSheet before handling, storing, or using this product**